STAYCOLD HD690

High Performance Single Door Upright Cooler

GREENSENSE FEATURES

SAVING ENERGY AND REDUCING LIFETIME COSTS

GreenSense
Powered by Energy Saving Technology

Digital Thermostat

For accurate temperature control and built in voltage protection.



LED Lighting

Illuminating the interior of the unit for maximum visibility.

EPA SNAP Approved

EcoMate Foam

Water based blowing agent that is non-flammable and has zero ODP.

Low-E Glass Door

Improved glass insulation lowers running costs and reduces condensation.

STAYCOLD International

Trust the Experience

STAYCOLD HD690
SINGLE DOOR COOLER

CABINET FEATURES

- Fully adjustable shelving
- LED lighting internal and canopy
- Energy saving EMD as standard
- High efficiency compressor
- High performance heat exchangers for powerful cooling
- Self-closing hinged doors
- Non-flammable, water based polyurethane blowing agent
- Double tempered, thermopane Low-E glass doors
- Reversible door action

Specifications	
Climate Class	5
Capacity (ltr)	530
Shelves	4
Cooling Type	Forced air
Voltage/Hz	220/50
Refrigerant	R134a
300ml Can Cap	640
330ml Bottle Cap	360

External Dimensions	
Height mm	2020
Width mm	690
Depth mm	635

Internal Dimensions	
Height mm	1380
Width mm	600
Depth mm	550

Packed Dimensions	
Height mm	2120
Width mm	700
Depth mm	645
Weight (kg)	117

Container Loading	
20'	27
40'	54

Code	Model	Description
2150	HD690	Std model with black trim and white Chromadek
2153	HD690-LFS	S/S sides, hydrocarbon (R290) gas, and grey trim
4150	SHD690	Stainless steel sides and solid door with grey trim

In the interests of continuous product development, specifications may be changed without notice.

1 Kakie Strachan Rd
Parys, South Africa

+27 (56) 819 8097

info@staycold.co.za

www.staycold.co.za

Staycold International (Pty) Ltd

STAYCOLD International