STAYCOLD SD1140

High Performance Double Sliding Door Upright Cooler

GREENSENSE FEATURES

SAVING ENERGY AND REDUCING LIFETIME COSTS

Digital Thermostat

For accurate temperature control and built in voltage protection.



LED Lighting

Illuminating the interior of the unit for maximum visibility.

EcoMate Foam

Water based insulation foam that is non-flammable and has zero ODP.

Low-E Glass Door

Improved glass insulation lowers running costs and reduces condensation.

STAYCOLD International

Trust the Experience

STAYCOLD SD1140
DOUBLE DOOR COOLER

CABINET FEATURES

- Fully adjustable shelving
- LED lighting internal and canopy
- Energy saving EMD as standard
- High efficiency compressor
- High performance heat exchangers for powerful cooling
- Reliable, self-closing sliding doors
- Non-flammable, water based polyurethane blowing agent
- Double tempered, thermopane Low-E glass doors

Specifications	
Climate Class	5
Capacity (ltr)	910
Shelves	8
Cooling Type	Forced air
Voltage/Hz	220/50
Refrigerant	R134a
300ml Can Cap	1024
330ml Bottle Cap	640

External Dimensions	
Height mm	2020
Width mm	1140
Depth mm	635

Internal Dimensions	
Height mm	1380
Width mm	1050
Depth mm	515

Packed Dimensions	
Height mm	2120
Width mm	1150
Depth mm	645
Weight kg	180

Container Loading	
20'	18
40'	36

1 Kakie Strachan Rd
Parys, South Africa

+27 (56) 819 8097

info@staycold.co.za

www.staycold.co.za

Staycold International (Pty) Ltd

STAYCOLD International

In the interests of continuous product development, specifications may be changed without notice.