



STAYCOLD HD690

High Performance
Single Door
Upright Cooler


GREENSENSE FEATURES

SAVING ENERGY AND REDUCING LIFETIME COSTS



Digital Thermostat

For accurate temperature control and built in voltage protection.



LED Lighting

Illuminating the interior of the unit for maximum visibility.



EcoMate Foam

Water based blowing agent that is non-flammable and has zero ODP.



Low-E Glass Door

Improved glass insulation lowers running costs and reduces condensation.



Trust the Experience



STAYCOLD HD690

SINGLE DOOR COOLER

CABINET FEATURES

- Fully adjustable shelving
- LED lighting internal and canopy
- Energy saving EMD as standard
- High efficiency compressor
- High performance heat exchangers for powerful cooling
- Self-closing hinged doors
- Non-flammable, methyl formate polyurethane blowing agent
- Double tempered, thermopane Low-E glass doors
- Reversible door action



Specifications		Internal Dimensions	
Climate Class [†]	CC3	Height mm	1380
Capacity (ltr)	530	Width mm	600
Shelves	4	Depth mm	550
Cooling Type	Forced air	Packed Dimensions	
Voltage/Hz	220/50	Height mm	2120
Refrigerant	R134a	Width mm	700
300ml Can Cap	640	Depth mm	645
330ml Bottle Cap	360	Weight (kg)	117
External Dimensions		Container Loading	
Height mm	2020	20'	27
Width mm	690	40'	54
Depth mm	635		

 1 Kakie Strachan Rd
Parys, South Africa

 +27 (56) 819 8097

 info@staycold.co.za

 www.staycold.co.za

 Staycold International (Pty) Ltd



[†] As defined by ISO 22044

In the interests of continuous product development, specifications may be changed without notice.